JONSERED MOBILE RECYCLING



Whatever your needs, we have the JONSERED loading crane for you







- High seat behind or to the side of the column, with option of no high seat
- Different column heights
- Variable lengths of arm systems, e.g. removable lengthwise in the container.
- Double telescopes
- Mechanical control using manually operated levers, electro-hydraulically using joysticks or remote control by radio.
- Load-sensing hydraulic system (lower energy requirement, long working life, minimal oil heating).
- Tiltomatic hoisting device used for automatic 180 degree parking of the stabilizer legs.
- Comprehensive additional equipment contained in the detail and accessories for use in recycling work









Jonsered mobile recycling product range

	Boom capacity kNm, net	Unloading m, max.	Weight Kg. with high seat and supports	Feature Std = Standard DT = Double telescope
	Std DT	Std DT	Std DT	Sta = Standard DT = Double telescope
J690	60	7.0	1200	
J820	80 72	7.5 9.6	1780 1900	
J920	95 89	7.9 9.7	1850 1960	
J1020	102 92	7.9 9.6	1930 2030	
J1120Z	106	7.7	1995	Transverse seat
J1300R	123 119	8.3 9.6	2050 2180	
J1320Z	129 108	7.9 9.4	2100 2265 2185 2350	Transverse seat/ with supports. ET 370 Transverse seat/ with supports. B 4820
J1420	134 128	7.9 9.6	2085 2225 2170 2310	With supports ET 370 With supports B 4820
J1620Z	165 152	7.8 9.3	2300 2520 2500 2720	Transverse seat/ with supports. ET 450 Transverse seat/ with supports. B 5500
J1820	173 165	7.8 9.0	2450 2800	
J2490	240 195	7.8 9.0	2675 3030	

Notwithstanding technical changes in execution, pictures and text.

